E-Disk® AltimaTM 2.5" PATA SSD

E-Disk® Altima™ SSDs set the standard for rugged and reliable data storage in extreme environments.



BiTMICRO® follows a rigorous testing procedure to deliver the highest quality, rugged solid state storage products. E-Disk Altima SSDs are tested to withstand extreme temperature, shock, vibration, humidity, and altitude.

E-Disk Altima SSDs protect user data with the highest level of security and meet the stringent requirements demanded by defense and industrial customers.

Powered by BiTMICRO EDSA™ flash I/O controller and LUNETA™ memory flash interface ASICs, E-Disk Altima SSDs boost system performance by eliminating seek time and latency.

Applications

E-Disk Altima SSDs are ideal for defense and industrial applications such as:

- Intelligence, Surveillance & Reconnaissance (ISR)
- Aviation & Avionics
- Industrial & Embedded
- Pipeline Inspection
- Medical Equipment
- Industrial Automation

Features

- Superior Ruggedness
- PowerGuard® Data Loss Protection (Optional)
- SecurErase® Power Loss Erase (Optional)
- SecurErase® Mobile Erase (Optional)
- Low Voltage Detection
- SecurErase® Military Sanitization

Copyright © 2019 BiTMICRO Networks, Inc. All rights reserved. BiTMICRO®, E-Disk®, Altima™, EDSA™, LUNETA™, SecurErase®, and PowerGuard® are trademarks or registered trademarks of BiTMICRO Networks, Inc. All other trademarks are the property of their respective owners. One GB equals 1,073,741,824 bytes when referring to solid state drive capacity. Product specifications are subject to change without prior notice. Standard and optional features may change and not all combination of features are implemented. The information stated in these product pages are thus informational only. To ensure that BiTMICRO meets your requirements, please contact us. For patent information, visit www.bitmicro.com/company/research-and-development.



Product Specifications

Physical	
Interface	ATA 133
Form Factor	2.5"
Dimensions (L x W x H)	3.955" x 2.75" x 0.374" to 1.00"
Weight	3.016 oz. to 9.065 oz.
Notes: - Size and weight numbers are approximate Height and weight may vary depending on configuration.	

Capacity	
SLC	20 GB to 300 GB
Note: Usable capacity.	

Performance	
Burst Rate	133 MB/s

Security	
SecurErase Standard Compliance	NISPOM DoD 5220.22-M NSA 130-2 Air Force AFSSI 5020 Army 380-19 IRIG-106 NISPOMSUP AFSSI 5020/2003 AFSSI 5020/2003 CLR NSA 9-12

Environmental (Operational)	
Temperature	Commercial: 0 to 70 °C Industrial: -40 to 85 °C
Shock	1,500 G
Vibration	16.4G rms
Altitude	-1,200 to 120,000 ft
Humidity	5 to 95% (non-condensing)

Power	
Voltage	5V DC (±5%)

Reliability	
Error Correction	Corrects 7 bits per 528 B
Write Endurance	6.74 years @ 100 GB/day write/erase cycles (20 GB)

Warranty	
Standard	1 year
Extended (Optional)	Up to 5 years

For more Information

Email: sales@bitmicro.com Call: +1 (888) 72-FLASH

Copyright © 2019 BiTMICRO Networks, Inc. All rights reserved. BiTMICRO®, E-Disk®, AltimaTM, EDSATM, LUNETATM, SecurErase®, and PowerGuard® are trademarks or registered trademarks of BiTMICRO Networks, Inc. All other trademarks are the property of their respective owners. One GB equals 1,073,741,824 bytes when referring to solid state drive capacity. Product specifications are subject to change without prior notice. Standard and optional features may change and not all combination of features are implemented. The information stated in these product pages are thus informational only. To ensure that BiTMICRO meets your requirements, please contact us. For patent information, visit www.bitmicro.com/company/research-and-development.